저작자표시 2.0 대한민국

이용자는 아래의 조건을 따르는 경우에 한하여 자유롭게

- 이 저작물을 복제, 배포, 전송, 전시, 공연 및 방송할 수 있습니다.
- 이차적 저작물을 작성할 수 있습니다.
- 이 저작물을 영리 목적으로 이용할 수 있습니다.

다음과 같은 조건을 따라야 합니다:

저작자표시. 귀하는 원저작자를 표시하여야 합니다.

- 귀하는, 이 저작물의 재이용이나 배포의 경우, 이 저작물에 적용된 이용허락조건을 명확하게 나타내어야 합니다.
- 저작권자로부터 별도의 허가를 받으면 이러한 조건들은 적용되지 않습니다.

저작권법에 따른 이용자의 권리는 위의 내용에 의하여 영향을 받지 않습니다.

이것은 [이용허락규약\(Legal Code\)](#)을 이해하기 쉽게 요약한 것입니다.

[Disclaimer](#)

공학석사 학위논문

Study on Spudcan
Soil-Structure Interaction of Wind
Turbine Installation Vessel

해상풍력발전기 전문설치선 스퍼드캔의
토질-구조 연성에 관한 연구

2015년 2월

서울대학교 대학원

조선해양공학과

JIN HAIBIN

Study on Spudcan Soil-Structure Interaction of Wind Turbine Installation Vessel

지도교수 장 범 선

이 논문을 공학석사 학위논문으로 제출함
2015년 2월

서울대학교 대학원
조선해양공학과
JIN HAIBIN

JIN HAIBIN의 석사학위논문을 인준함
2015년 2월

위 원 장 양 영 순 (인)

부위원장 신 종 계 (인)

위 원 노 명 일 (인)

Abstract

Study on Spudcan Soil–Structure Interaction of Wind Turbine Installation Vessel

JIN HAIBIN

Dept. of Naval Architecture and Ocean Engineering

The Graduate School

Seoul National University

A jack-up type WTIV (Wind Turbine Installation Vessel) is necessary to install offshore wind turbines. To avoid the effect of waves when installing wind turbines, WTIV should be lifted clear of the water. It is usually supported by several independent truss legs. The spudcans are the inverted cones mounted under each leg of the WTIV which provides stability to both vertical and lateral forces.

Before WTIV can operate at a given location, a site-specific

assessment should be performed. A risk exists when lifting the WTIV at the site with critical soil conditions especially the strata with strong soil overlying soft soil. Instability may occur when the leg is penetrating a layer of strong soil into underlying soft soil by a rapid leg penetration which is known as punch-through. Thus, it is significant to accurately predict the penetration depth and ensure the stability during spudcan penetration. To avoid punch-through type of failure, prediction of ultimate bearing capacity and corresponding penetration depth is required. For this purpose, the conventional analysis recommended in the SNAME guideline is introduced in this paper. Soil conditions of OW-3 and OW-4 in the wind farm in the Southwest Sea of South Korea are used.

WTIV structural assessment of its ability to withstand a storm condition should also be performed. The complex stress and strain state of soil under the spudcan is commonly simplified to a value of soil stiffness that is input as a boundary condition into the structural analysis. These boundary conditions include pinned footings, fixed footings, spring footings based on both SNAME and Model B. Soil-structure interaction effects can be considered when the boundary conditions are set as springs with a corresponding yield surface.

A jack-up structural analysis is performed with three kinds of boundary conditions. Structural analysis results with SNAME springs are compared to those with Model B in previous studies. Structural analysis results with SNAME and Model B are almost the same.

Structural analysis of WTIV with four legs is also performed with pinned footings, fixed footings and spring footings. From the results, a reduction in stresses of the members at leg-hull connection can be found. Yield first occurs in the leeward spudcan and once yield occurs moment in the spudcan decreases. Besides, soil strength and preload have significant impacts on structural analysis results. Spudcan loads will be redistributed if soil-structure interaction is taken into account in a structural analysis.

Keywords : Spudcan, Bearing capacity, Soil-structure interaction, Soil stiffness, Yield surface

Student Number : 2012-23988

Contents

1.	Introduction.....	1
1.1.	Research Background and Objective.....	1
1.2.	State of Art	9
2.	Spudcan Bearing Capacity.....	12
2.1.	Spudcan.....	12
2.2.	Bearing Capacity.....	13
3.	Soil Condition	21
3.1.	Wind Farm.....	21
3.2.	Soil Conditions of OW-1~8	23
4.	Spudcan Penetration during Preloading	26
5.	Soil-Structure Interaction.....	29
5.1.	Features of Soil-Structure Interaction.....	29
5.2.	Soil-Structure Interaction in SNAME	34
5.3.	Soil-Structure Interaction in Model B.....	38
6.	Structural Analysis Considering Soil-Structure Interaction.....	44
6.1.	An Example of Jack-Up Structural Analysis	44
6.1.1.	Jack-up Model	44
6.1.2.	Jack-Up Structural Analysis Results	47
6.2.	WTIV structural analysis	58
6.2.1.	WTIV Model.....	58
6.2.2.	Boundary Condition	60
6.2.3.	WTIV Structural Analysis Results	62
7.	Conclusion.....	76
	Reference.....	79

List of Figures

Fig. 1 Wind Turbine Installation Vessel (WTIV)	1
Fig. 2 Spudcan.....	3
Fig. 3 WTIV operation procedure	5
Fig. 4 Boundary conditions in structural analysis.....	6
Fig. 5 Plane frame jack-up structure.....	7
Fig. 6 Spudcan load paths of V-M envelope.....	9
Fig. 7 3D designed spudcan shape.....	13
Fig. 8 Spudcan simplification.....	14
Fig. 9 General shear	16
Fig. 10 Squeezing.....	17
Fig. 11 Punch-through failure (Arabdrill 19).....	18
Fig. 12 Load-penetration depth curve	19
Fig. 13 Punch-through.....	20
Fig. 14 Wind farm position	22
Fig. 15 Location of boreholes OW-1~8.....	22
Fig. 16 Columnar sections of drilling holes	23
Fig. 17 Spudcan load-penetration depth curve	27
Fig. 18 Plane view of jack-up	30
Fig. 19 Spudcan foundation and sign conventions for loads and displacements	30
Fig. 20 Yield surface (Martin, C.M., 1994)	32
Fig. 21 Hardening law.....	33
Fig. 22 Nonlinear spudcan rotational behavior.....	34
Fig. 23 Soil-structure interaction procedure in SNAME.....	35
Fig. 24 Soil-structure interaction procedure in Model	39
Fig. 25 Plane frame jack-up model with springs	45
Fig. 26 Spudcan load results of this paper	50
Fig. 27 The existing spudcan load results	52
Fig. 28 Combined stress results	54
Fig. 29 Hull sway	55
Fig. 30 Hull deformation ($H_{env}=5$ MN)	57
Fig. 31 WTIV structural analysis model.....	59

Fig. 32 Elastic soil stiffness factors of SNAME	61
Fig. 33 Spudcan loads in OW-3 (joint 2338 & joint 2705)	64
Fig. 34 Spudcan loads in OW-3 (joint 3439 & joint 3702)	65
Fig. 35 Spudcan loads in OW-4 (joint 2338 & joint 2705)	67
Fig. 36 Spudcan loads in OW-4 (joint 3439 & joint 3702)	68
Fig. 37 Spudcan load path of H-M for joint 2338	70
Fig. 38 Spudcan load paths of V-M for OW-4.....	71
Fig. 39 Spudcan load paths of H-M for OW-4	72
Fig. 40 WTIV UC ratio results	75

List of Tables

Table 1 The symbols of soil classification (Das, B.M., 2009)	24
Table 2 Soil properties of OW-3	25
Table 3 Soil properties of OW-4	25
Table 4 Spudcan penetration results	28
Table 5 Data for the example jack-up model	46
Table 6 Clay properties	46
Table 7 Elastic stiffnesses of SNAME	47
Table 8 Elastic stiffnesses of Model B	47
Table 9 Vertical load without environment load	60
Table 10 Initial elastic stiffnesses of SNAME	61
Table 11 Data for yield surface of joint 2338	70
Table 12 Maximum unity check ratio ($H_{env}=12$ MN in OW-4)	75

NOMENCLATURE

A	= Spudcan effective bearing area
A_s	= Spudcan laterally projected embedded area
B	= Effective spudcan diameter
a, b	= Bearing capacity squeezing factor
c_u	= Undrained cohesive shear strength at $D+B/4$ below mudline
c_{uo}	= Undrained cohesive shear strength at maximum bearing area (D below mudline)
c_{ul}	= Undrained cohesive shear strength at spudcan tip
d_c, d_q, d_γ	= Bearing capacity depth factor
D	= Distance from mudline to spudcan maximum bearing area
F'_o	= Effective overburden pressure due to back-flow at depth of uppermost part of bearing area
F_V	= Vertical foundation capacity
$F_{V,b}$	= Ultimate vertical bearing capacity assuming the footing bears on the surface of the lower clay layer with no back-flow
H	= Distance from spudcan maximum bearing area to weak strata below
I	= Height of soil column above spudcan
K_s	= Coefficient of punching shear
N_c, N_q, N_γ	= Bearing capacity factor
p'_o	= Effective overburden pressure at depth, D , of maximum bearing area
R	= Effective spudcan radius

s_c, s_q, s_γ	= Bearing capacity shape factor
T	= Thickness of weak clay layer underneath spudcan
V	= Volume of soil displaced by spudcan
V_{L0}, V_0	= Maximum vertical foundation load during preloading
W	= Weight of soil plug
γ'	= Submerged unit weight of soil
ϕ	= Angle of internal friction for sand

1. Introduction

1.1. Research Background and Objective

With the rapid growth of the demand for new energy, people gradually take interested in wind energy source, especially in offshore wind energy source in recent decades. To construct a wind farm in the sea a specialized Wind Turbine Installation Vessel (WTIV) as shown in Fig. 1 is needed due to its mobility and cost-effectiveness. There are mainly three parts in WTIV, hull, equipment, legs and footings.

Fig. 1 Wind Turbine Installation Vessel (WTIV)

WTIV has a slender ship shaped hull. The hull provides buoyancy and supports the weight of the legs and footings, equipment, and variable loads. It is a self-propelling ship carrying several wind turbines to the site where wind turbines are installed.

The equipment required to satisfy the mission of the WTIV. There are three main parts of equipment on a WTIV, the marine equipment, mission equipment, and elevating equipment. During installing wind turbines, WTIV should be lifted above the sea water to achieve a steady work environment avoiding the effects of waves. The legs are moved up and down through the hull utilizing a rack and pinion jacking system.

In general, WTIV has several latticework legs, which are supported by individual footings. These footings are usually inverted cones called spudcan as shown in Fig. 2. To ensure the safety of WTIV during the operation, the spudcans must penetrate into the seabed until a safe condition is achieved. If the stabilizing effect of gravity loads is not enough for wave loads, it is possible that overturning of WTIV may happen during a severe storm condition.

Fig. 2 Spudcan

The operation procedure of WTIV is shown in Fig. 3. It is self-propelled to the location where wind turbines are to be installed. After arriving at the site, legs are lowered down and WTIV is preloaded to ensure the soil is capable of withstanding the maximum expected spudcan reaction without experiencing additional leg penetration or soil failure. This procedure is done by lifting the hull clear of the water and pumping the sea water into the ballast tanks. Preloading ensures that some level of spudcan fixity is achieved.

During preloading period, it is critical to estimate the spudcan penetration depth correctly. It is directly relevant to the leg design which is an important value for leg length design. What's more, at the location, if there is a soft soil layer underlying a strong soil layer, an unpredicted sudden penetration may happen, which is

called punch-through. Thus, before preloading, a site-specific estimation of spudcan penetration behavior is necessary.

After unloading, WTIV is subjected to environment loads. Structural analysis should be done to ensure the safety of the structure under extreme storm condition. In this situation, the structure suffers from maximum wind, wave and current, and the spudcans experience a load combination of vertical and horizontal loads and moments (see Fig. 3(d)). The soil around the spudcans provides some fixity which is a boundary condition when structural analysis is performed. It is usually to assume the spudcans offer no resistance to moment, i.e. behaving like a pin. However, since the spudcans are often embedded to a significant depth below the seabed, especially in soft clay, they indeed offer some level of rotational restraint. In this situation, vertical, horizontal and rotational springs can be given at the spudcans to consider real soil behaviors. Soil stiffness is given for each spring constant.

Fig. 3 WTIV operation procedure

The maximum bending moment at the top of the leg and load distribution between different spudcans depend on the assumption of boundary conditions (see Fig. 4) given at spudcans. On the

contrary, load combination of each spudcan which can be achieved after structural analysis influences the soil stiffness. Therefore, a soil–structure interaction should be considered during structural analysis.

Fig. 4 Boundary conditions in structural analysis

A plane frame jack-up structure is shown in Fig. 5. It is a simplified two dimensional jack-up structural analysis model. In this model, there are two windward spudcans and one leeward spudcans, so leg properties as well as environment load and self-weight in the windward spudcan are twice of those in the leeward spudcan. Pinned footings, spring footings and fixed footings can be given as boundary conditions at spudcan position.

Fig. 5 Plane frame jack-up structure

When the environment load acts on the structure, spudcan load path results are different based on different boundary conditions. Fig. 6 illustrates the spudcan load path results for different kinds of boundary conditions. From the figure, it can be seen that vertical load in the leeward spudcan increases, while it decreases in the windward spudcan. If the boundary conditions are given as spring footings, soil-structure interaction effect can be considered in the structural analysis using yield surface. Moments in the windward and leeward spudcan decrease immediately after the load path reach the yield surface. This is due to that when the spudcan load combination reaches its capacity, that is reaches the yield surface, the spudcan fixity will decrease gradually.

(a) Spudcan load paths of pinned footings

(b) Spudcan load paths of fixed footings

(c) Spudcan load paths of spring footings

- $\rightarrow$ **Windward spudcan**
 — $\rightarrow$ **Leeward spudcan**

Fig. 6 Spudcan load paths of V–M envelope

There is also a spudcan in a jack-up rig. Thus, the same consideration should be taken when a site-specific spudcan penetration estimation and structural analysis are performed. Above all, in this paper, there are mainly two objectives to be studied. One is spudcan penetration during preloading, and the other one is structural analysis during operation considering soil–structure interaction.

1.2. State of Art

Studies on the spudcan have been hot issues for both jack-up rig

and WTIV. Prediction of the spudcan penetrations is important in the process of installation. During the installing and operating process in multi-layered soil conditions, if there is a strong layer overlying soft layer, punch-through may be encountered. Conventional solutions (Hansen J.B., 1970; SNAME, 2002) are applications of bearing capacity equations for homogeneous and multi-layered soil conditions. Some numerical analyses have also been done to compare the results with those using conventional solutions (Jun Zhao et al., 2011; Lindita Kellezi et al., 2012).

During storm conditions, to perform structural analysis of jack-up rig or WTIV, researchers have tended to concentrate on models that the spudcan is simplified as a rigid body attached to vertical, horizontal and rotational springs (Martin, C.M. et al. 2001). The most fundamental models is the pinned footing (infinite vertical and horizontal stiffnesses, zero rotational stiffness). It is still widely used in jack-up and WTIV analyses, but it is idealized and conservative. Thus, some level of rotational stiffness as well as soil-structure interaction effect should be considered. It is widely acknowledged that predictions of structural performance should take account of nonlinear spudcan behavior, especially nonlinear

rotational behavior. This can be achieved by using a tangent stiffness method (Model B in clay and Model C in sand) (Martin, C.M., 1994; Ngo–Tran, C.L., 1996; Martin, C.M. et al., 2000; Martin, C.M. et al., 2001) or a secant stiffness method (SNAME, 2002; Cassidy, M.J. et al., 2002; Keith Nelson, 2000).

There have been some studies on structural analysis with tangent stiffness method (Martin, C.M. et al., 1999; ZHANG Jian et al., 2012). However, there is no comparison about structural analysis results between Model B and SNAME.

In this paper, conventional method is used to predict spudcan penetration behavior based on real soil data in the Southwest Sea of South Korea. Soil stiffness used in structural analysis of jack–up or WTIV is achieved with SNAME and Model B. Elastic stiffness factor taking spudcan penetration depth into account is also considered. An example of jack–up structural analysis considering soil–structure interaction is performed. Structural analysis results with SNAME springs are compared to those with Model B (Martin, C.M. et al., 1999). An in–place WTIV structure is also analyzed with SNAME springs, and analysis results will be shown and discussed in this paper.

2. Spudcan Bearing Capacity

In this chapter, a spudcan with a rectangular shape is to be introduced. Also, the conventional method used to estimate spudcan ultimate bearing capacity in both homogeneous soil conditions and layered soil profiles is also mentioned.

2.1. Spudcan

There are many kinds of spudcan shapes, circle, rectangular, hexagonal shapes, etc. Legs usually are connected at circular spudcan sides or on the top of a rectangular spudcan. Thus, if the distance between the chords is fixed, a rectangular spudcan may have a larger bearing area, which is beneficial to spudcan bearing capacity.

Due to that hull size of the WTIV is limited, distance between the chords is also limited. To maximize the spudcan bearing capacity, a rectangular spudcan is used in introduced in this paper shown in Fig. 7. Its maximum bearing area is 112.8 m^2 .

(a)

(b)

Fig. 7 3D designed spudcan shape

2.2. Bearing Capacity

In this paper, the conventional method recommended in the current design guidelines Society of Naval Architects and Marine

Engineers (SNAME) is performed based on applications of bearing capacity equations for homogeneous soil conditions and modified procedures for multi-layered soil profiles. Spudcan is a very complicated steel structure, and thus it is necessary to be simplified to a cylinder shape whose maximum bearing area and volume are the same as the designated spudcan. In Fig. 8, A stands for maximum bearing area and B is the equivalent diameter of the simplified spudcan.

Fig. 8 Spudcan simplification

There are totally three kinds of basic failure mechanisms in prediction of spudcan bearing capacities in layered soils:

- General shear
- Squeezing
- Punch-through

➤ **General shear**

General shear failure mechanism is calculated based on Terzaghi's ultimate bearing capacity equation considering spudcan shape and roughness. Ultimate bearing capacity of each soil layer are calculated with equations (1) and (2). In general, this kind of failure mechanism occurs if soil parameters of subsequent layers do not vary significantly. If undrained shearing strength (c_u) or internal frictional angle (φ) is not a constant, an average of soil strength parameter of each layer is used. In the process of spudcan penetration, due to unsafety of soil bodies around, back-flow may happen. If it happens, maximum vertical foundation load during installing V_{L0} can be calculated using equation (3).

$$F_v = (c_u N_c s_c d_c + p'_o)A \quad (1)$$

$$F_v = (0.5\gamma' B N_\gamma s_\gamma d_\gamma + p'_o N_q s_q d_q)A \quad (2)$$

$$V_{L0} = F_v - F'_o A + \gamma V \quad (3)$$

Fig. 9 General shear

➤ Squeezing

Squeezing failure mechanism is calculated in the layer of soft clay overlying strong soils including hard clay and sand. Clay layer is squeezed when the spudcan penetrates deep into the soil so that vertical loads are dispersed to subsequent layer. Spudcan bearing capacities can be estimated with equations (4) and (5) both with full and no back-flow.

$$Q_v = A \left\{ \left(a + \frac{bB}{T} + \frac{1.2D}{B} \right) c_u + p_o' \right\} \geq (c_u N_c s_c d_c + p_o') A \quad (4)$$

$$Q_v = A \left\{ \left(a + \frac{bB}{T} + \frac{1.2D}{B} \right) c_u \right\} + V\gamma' \geq (c_u N_c s_c d_c) A + V\gamma' \quad (5)$$

Fig. 10 Squeezing

➤ Punch-through

Punch-through failure mechanism is the most common and dangerous. It probably happens when firm sand overlies soft clay. When the leg of WTIV is being lowered and fixed to the seabed, if punch-through type of failure occurs, the WTIV will lose stability and equilibrium. A punch-through failure is shown in Fig. 11.

Fig. 11 Punch-through failure (Arabdrill 19)

In Fig. 12, it can be seen that with the load increasing, penetration depth increases gradually. However, if there is a soft soil layer with increased penetration depth, bearing capacities in each depth suddenly reduces, and a rapid penetration may happen at a certain load. It may cause a disaster in jack-up rig or WTIV structure.

Fig. 12 Load–penetration depth curve

Thus, punch-through should be taken particular care of. In estimating the spudcan penetration behavior in layered soil strata in which punch-through is likely to happen, two methods of analysis are commonly employed. The projected area method is applied which uses the concept of a fictitious spudcan of increased area at the interface between a strong layer and a weaker underlying one.

$$F_v = F_{v,b} - W \quad (6)$$

$$F_v = F_{v,b} - W - AI\gamma' \quad (7)$$

Fig. 13 Punch-through

Thus, for a load spreading under a slope of $1:n$, ultimate bearing capacity of the spudcan can be calculated by equation (6) for no back-flow and equation (7) for full back-flow. According to model test data n is suggested 3~5, whereas actual spudcan penetration data are available which suggest a higher spread.

In case of $n = \infty$, a vertical punching shear mechanism is calculated which uses the concept that maximum bearing area of fictitious spudcan is the same as that of the real spudcan. It is generally applied for stiff or hard clay overlying soft to firm clay.

3. Soil Condition

In this chapter, soil conditions of a wind farm located in the Southwest Sea of South Korea are introduced. Soil properties of selected boreholes used in spudcan penetration analysis and soil–structure interaction is also involved.

3.1. Wind Farm

The geotechnical investigation of the wind farm where wind turbines will be installed was performed in the Southwest Sea of South Korea. It is near Wansan–gu as shown in Fig. 14.

Eight boreholes were drilled to investigate the soil properties of the area. The water depths vary from about 10 m to 20 m. Most of drilling holes were in soft ground except for OW–1, 2, 5. Location of boreholes OW–1~8 is shown in Fig. 15.

Fig. 14 Wind farm position

Fig. 15 Location of boreholes OW-1~8

3.2. Soil Conditions of OW-1~8

Based on the investigation results, columnar sections of drilling holes OW-1~8 as shown in Fig. 16 were achieved. Soil profiles were shown with penetration depth in the figure.

Fig. 16 Columnar sections of drilling holes

The symbols of soil classification used in Fig. 16 can be seen in Table 1.

Table 1 The symbols of soil classification (Das, B.M., 2009)

Soil symbols		Liquid limit (LL) symbols		Gradation symbols	
G	Gravel	H	High LL (LL>50)	W	Well-graded
S	Sand				
M	Silt	L	Low LL (LL<50)	P	Poorly-graded
C	Clay				

Based on Table 1, for example, SM stands for sandy silt; SP–SM stands for poorly-graded sand with silt; ML stands for sandy silt; CL stands for lean clay. Besides, WR represents weathered rock.

It can be seen in Fig. 16 most soil conditions are soft in the wind farm area. In this paper, OW–3 and OW–4 are taken as an example to assess the spudcan penetration depth and to perform structural analysis considering soil–structure interaction. OW–3 stands for a soft soil condition from seabed to the depth of about 30 m, while OW–4 stands for a soil condition where possible clay squeezing and punch-through may happen.

Soil strength parameters, ϕ for sand and c_u for clay, were derived based on the results of Cone Penetration Tests (CPTs). γ is unit weight of soil, but it is usually used as submerged unit weight to calculate spudcan bearing capacities removing the effect of the

unit weight of water. Detailed soil properties of OW-3 and OW-4 are listed in Table 2 and Table 3.

Table 2 Soil properties of OW-3

D	Classification	γ	c_u	ϕ	ν
0.0~19.0	Sandy silt	17.5	22.0	0.0	0.38
19.0~25.3	Silty clay	17.0	25.0	0.0	0.40
25.3~29.5	Silt	17.5	22.0	0.0	0.38
29.5~36.5	Granular~Neutral sand (with silt)	18.0	0.0	25.0	0.36

Table 3 Soil properties of OW-4

D	Classification	γ	c_u	ϕ	ν
0.0~6.0	Sandy silt	17.5	22.0	0.0	0.38
6.0~9.0	Silty clay	17.0	25.0	0.0	0.40
9.0~19.3	Silty sand	18.0	0.0	26.0	0.35
19.3~24.8	Silt	17.0	25.0	0.0	0.40
24.8~36.0	Silty clay	17.0	25.0	0.0	0.40

4. Spudcan Penetration during Preloading

In this chapter, spudcan penetration results during preloading based on the spudcan area and soil conditions in the previous chapters are involved. The preload in this chapter used to evaluate penetration depth is 50 MN.

In the previous Chapter 2, ultimate spudcan bearing capacities can be achieved with three kinds of failure mechanisms. Spudcan load–penetration depth curve was shown in Fig. 17, based on maximum preloads and ultimate spudcan bearing capacities at each penetration depth.

From Fig. 15 under a preload of 50 MN, the spudcan penetrates 8.72 m in OW–3 and 29.04 m OW–4, respectively. When the spudcan penetrates into the seabed, soils around the spudcan will fall back onto the top of the spudcan due their instability, which is called back–flow. In this paper, a full back–flow is assumed. Thus, ultimate spudcan bearing capacity consists of preload and the weight of back–flow.

It can be seen in Fig. 17, ultimate spudcan bearing capacities are 54.76 MN in OW–3 and 71.59 MN in OW–4, respectively, under a preload of 50 MN, which means that the weight of back–flow are

4.76 MN in OW-3 and 21.59 MN in OW-4.

Fig. 17 Spudcan load-penetration depth curve

Some spudcan penetration results are listed in Table 4. There is a significant difference in D in the two kinds of soil conditions. Due to the second clay layer was squeezed, its penetration stopped at only 8.72 m which is just before entering the third sand layer in OW-3. However, because of that OW-4 consists of soft soils, it should be penetrated deep into the seabed.

Depth factor is defined as the ratio of penetration depth and spudcan effective diameter. The depth factor values, D/B , are listed in Table 4. D/B is used to find an elastic soil stiffness factor which is further used in structural analysis. In general, elastic soil stiffness factor increases with D/B increasing.

Table 4 Spudcan penetration results

	F _v (MN)	D (m)	B (m)	D/B
OW-3	71.59	29.04	11.99	2.42
OW-4	54.76	8.72	11.99	0.73

5. Soil-Structure Interaction

In this chapter, features of soil-structure interaction are involved. Two kinds of methods, which are presented in SNAME and Model B for clayey soils, are introduced to consider soil-structure interaction in the structural analysis.

5.1. Features of Soil-Structure Interaction

In general, jack-up rig has three legs to support the hull and it is a triangular shape from plan view (see Fig. 18). Environment load including the effect of wave, wind, and current is represented as a quasi-static load. If environment load is given in a direction like Fig. 18, the three dimensional jack-up structure model can be simplified to a two dimensional model.

Fig. 18 Plane view of jack-up

As shown in Fig. 19, loads (V, M, H) and displacements (ω, θ, u) in the spudcan are always referred to the original position.

Fig. 19 Spudcan foundation and sign conventions for loads and displacements

In a force-resultant spudcan model, there is an empirical

expression in three dimensional vertical, horizontal and moment loading space $(V, M/R, H)$, which is called yield surface (see Fig. 20(a)). The yield surface represents the combined bearing capacity surface of a spudcan at a specific vertical plastic penetration.

As shown in Fig. 20(b), after preloading (vertical load only) is finished, the spudcan reaches its maximum vertical load and the size of the yield surface is decided by this load. Once the yield surface is established, any changes of load combination will result only in elastic deformation within the surface, and in elasto-plastic deformation on the surface. After unloading, an elastic change in load combination start to happen, and the load combination may reach or even fall outside the yield surface, with the environment load increasing.

(a)

(b)

Fig. 20 Yield surface (Martin, C.M., 1994)

The hardening law is an empirical displacement–hardening expression to define the variation of the size of the yield surface. In general, the yield surface is cigar–shaped, and its shape is assumed constant. However, it expands as shown in Fig. 21 with the uniaxial vertical capacity solely to vertical plastic penetration. Thus, the hardening law is represented by the vertical load–penetration response which is involved in Chapter 4.

Fig. 21 Hardening law

For a footing under combined load, the spudcan behaves elastically within the yield surface. After the load combination reaches yield, the spudcan will behave elasto-plastically. This can be described as two methods: an iterative analysis with secant stiffness presented in SNAME, and an incremental analysis with tangent stiffness mentioned in Model B (see Fig. 22). Initial state and final state of the load combination are used in a secant stiffness method, while initial state and a load combination increment instead of the final state are used in a tangent stiffness method.

Fig. 22 depicts a nonlinear spudcan rotational behavior, which describes the difference between the two methods. Detailed information about soil-structure interaction procedure will be

follow in the next two parts.

Fig. 22 Nonlinear spudcan rotational behavior

5.2. Soil-Structure Interaction in SNAME

Soil-structure interaction is taken into account as the secant stiffness method using SNAME. Fig. 23 depicts the calculation procedure of soil-structure interaction.

Fig. 23 Soil–structure interaction procedure in SNAME

In the beginning, vertical and horizontal stiffnesses can be estimated with equation (8) and equation (9) from the Boussinesq elastic solutions for a rigid circular plate on an elastic half-space. An initial estimate for rotational stiffness is given as equation (10). Effects of embedment of the spudcan on the elastic spring stiffnesses K_1, K_2, K_3 are also considered which can be achieved

from the load–penetration depth curve.

$$K_v = \frac{2G_v B}{(1-\nu)} \quad (8)$$

$$K_h = \frac{16G_h B(1-\nu)}{(7-8\nu)} \quad (9)$$

$$K_r = \frac{G_r B^3}{3(1-\nu)} \quad (10)$$

$$\begin{Bmatrix} V \\ H \\ M \end{Bmatrix}^e = \begin{bmatrix} K_1 K_v & 0 & 0 \\ 0 & K_2 K_h & 0 \\ 0 & 0 & K_3 K_r \end{bmatrix} \begin{Bmatrix} w \\ u \\ \theta \end{Bmatrix}^e \quad (11)$$

Then structural analysis can be first done including vertical, horizontal and rotational stiffnesses to the structure model and the gravity and factored environment load as a quasi–static load. Vertical, horizontal and rotational stiffnesses at the spudcan are shown in equation (11). Reaction forces of each spudcan can be achieved after the first structural analysis. If the load combination (V, M, H) lies outside the yield surface ($f < 0$), the linear rotational stiffness at the spudcan should be reduced arbitrarily and iteratively until the load combination lies on the surface ($f = 0$). The yield surface can be expressed by equation (12). If the load

combination lies inside the yield surface ($f > 0$), it means spudcan behavior is elastic.

$$f = 16 \left[\frac{V}{V_{L0}} \right]^2 \left[1 - \frac{V}{V_{L0}} \right] \left[\left[1 - \frac{V}{V_{L0}} \right] - \left[\frac{H}{H_{L0}} \right]^2 - \left[\frac{M}{M_{L0}} \right]^2 \right] \quad (12)$$

where $H_{L0} = c_{uo}A + (c_{uo} + c_{ul})A_s$, $M_{L0} = 0.1V_{L0}B$.

In this situation, the initial rotational stiffness should be reduced by a reduction factor f_r

$$f_r = \sqrt{(1 - r_f)} + 0.1e^{100(r_f - 1)} \quad (13)$$

where r_f , which is the measure of the proximity of the spudcan load combination to the yield surface, is defined as the failure ratio:

$$r_f = \frac{\left\{ \left[\frac{H}{H_{L0}} \right]^2 + \left[\frac{M}{M_{L0}} \right]^2 \right\}^{0.5}}{4 \left[\frac{V}{V_{L0}} \right] \left[1 - \frac{V}{V_{L0}} \right]}.$$

It should be noted that $f < 0$ indicates a bearing failure. Thus, the value of the yield function should not be less than zero.

5.3. Soil-Structure Interaction in Model B

Soil–structure interaction in Model B is called as tangent stiffness method. The load combination increment ($\delta V, \delta M, \delta H$) is used in Model B instead of the load combination (V, M, H) in SNAME. The calculation procedure is shown in Fig. 24.

Structural analysis is performed with an environment load increment. The stiffness matrix used in structural analysis depends on the initial state and trial state of the spudcan load combination before and after structural analysis.

When considering a new increment, it assumes that the increment is elastic and makes a trial solution. There are six possible cases of spudcan behavior:

- Case 1: $f_{initial} < 0, f_{trial} < 0$
- Case 2: $f_{initial} < 0, f_{trial} = 0$
- Case 3: $f_{initial} < 0, f_{trial} > 0$
- Case 4: $f_{initial} = 0, f_{trial} < 0$
- Case 5: $f_{initial} = 0, f_{trial} = 0$
- Case 6: $f_{initial} = 0, f_{trial} > 0$

Fig. 24 Soil–structure interaction procedure in Model

For Case 1, Case 2, Case 4 and Case 5, elastic stiffness matrix (equation (14)) is used, while for Case6, elasto–plastic stiffness matrix is used. However, for Case 3, both elastic and elasto–plastic

stiffness should be used, because the spudcan behaves elastically and elasto-plastically in this case. K_1, K_2, K_3, K_4 are the elastic stiffness factors considering spudcan penetration depth.

$$\begin{Bmatrix} \delta V \\ \delta H \\ \delta M \end{Bmatrix}^e = \begin{bmatrix} K_1 GR & 0 & 0 \\ 0 & K_2 GR & K_4 GR^2 \\ 0 & K_4 GR^2 & K_3 GR^3 \end{bmatrix} \begin{Bmatrix} \delta z \\ \delta h \\ \delta \theta \end{Bmatrix}^e \quad (14)$$

Together with the yield surface (equation (15)), soil-structure interaction effect can be included in the structural analysis. In this paper, load combination within the yield surface is considered with Model B.

$$f = \left(\frac{H}{h_0 V_0} \right)^2 + \left(\frac{M/2R}{m_0 V_0} \right)^2 - 2 \left(e_1 + e_2 \left(\frac{V}{V_0} \right) \left(\frac{V}{V_0} - 1 \right) \right) \left(\frac{H}{h_0 V_0} \right) \left(\frac{M/2R}{m_0 V_0} \right) \quad (15)$$

$$- \left[\frac{(\beta_1 + \beta_2)^{(\beta_1 + \beta_2)}}{\beta_1^{\beta_1} \beta_2^{\beta_2}} \right]^2 \left(\frac{V}{V_0} \right)^{2\beta_1} \left(1 - \frac{V}{V_0} \right)^{2\beta_2} = 0$$

where $m_0 = 0.083$, $h_0 = 0.127$, $e_1 = 0.518$, $e_2 = 1.180$, $\beta_1 = 0.764$, $\beta_2 = 0.882$.

Equation (16) describes elasto-plastic relationship. The elasto-plastic increment displacement vector during yielding contains

elastic, plastic and coupled components (Martin, C.M., 1994).

$$\begin{aligned} \begin{Bmatrix} \delta w \\ \delta u \\ R\delta\theta \end{Bmatrix}^{ep} &= \begin{bmatrix} C_1 & 0 & 0 \\ 0 & C_2 & C_4 \\ 0 & C_4 & C_3 \end{bmatrix} \begin{Bmatrix} \delta V \\ \delta H \\ \delta M/R \end{Bmatrix} + \xi \begin{Bmatrix} \xi_a \cdot \partial f / \partial V \\ \partial f / \partial H \\ \partial f / \partial (M/R) \end{Bmatrix} + \\ &\xi \cdot \zeta_a \cdot \frac{\partial f}{\partial V} \begin{bmatrix} dC_1/dz & & \\ & dC_2/dz & dC_4/dz \\ & dC_4/dz & dC_3/dz \end{bmatrix} \begin{Bmatrix} V + \delta V \\ H + \delta H \\ M/R + \delta M/R \end{Bmatrix} \end{aligned} \quad (16)$$

where C_1, C_2, C_3, C_4 are flexibility factors given by:

$$\begin{aligned} C_1 &= \frac{1}{GR} \cdot \frac{1}{K_1} \quad , \quad C_2 = \frac{1}{GR} \cdot \frac{K_3}{K_2 K_3 - K_4^2} \quad , \quad C_3 = \frac{1}{GR} \cdot \frac{K_2}{K_2 K_3 - K_4^2} \quad , \\ C_4 &= \frac{1}{GR} \cdot \frac{K_4}{K_4^2 - K_2 K_3} \end{aligned}$$

Spudcan behaves elasto-plastically when the load combination remains on the yield surface, so there is a consistency condition

$$\mathcal{F} = 0 \quad (17)$$

From equations (16) and (17), the overall elasto-plastic incremental form of Model B can be expressed in 7×7 matrix form as

$$\begin{bmatrix}
1 \text{ or } 0 & 0 & 0 & 0 \text{ or } 1 & 0 & 0 & 0 \\
0 & 1 \text{ or } 0 & 0 & 0 & 0 \text{ or } 1 & 0 & 0 \\
0 & 0 & 1 \text{ or } 0 & 0 & 0 & 0 \text{ or } 1 & 0 \\
C_1 & 0 & 0 & -1 & 0 & 0 & B_{47} \\
0 & C_2 & C_4 & 0 & -1 & 0 & B_{57} \\
0 & C_4 & C_3 & 0 & 0 & -1 & B_{67} \\
\frac{\partial f}{\partial V} & \frac{\partial f}{\partial H} & \frac{\partial f}{\partial(M/R)} & 0 & 0 & 0 & B_{77}
\end{bmatrix}
\begin{Bmatrix}
\delta V \\
\delta H \\
\delta M / R \\
\delta z \\
\delta h \\
R \delta \theta \\
\xi
\end{Bmatrix}
=
\begin{Bmatrix}
inc_1 \\
inc_2 \\
inc_3 \\
0 \\
0 \\
0 \\
0
\end{Bmatrix} \quad (18)$$

where

$$\begin{aligned}
B_{47} &= \xi_a \frac{\partial f}{\partial V} \left(1 + [V + \delta V] \frac{dC_1}{dz^p} \right) \\
B_{57} &= \frac{\partial f}{\partial H} + \xi_a \frac{\partial f}{\partial V} \left([H + \delta H] \frac{dC_2}{dz^p} + [M / R + \delta M / R] \frac{dC_4}{dz^p} \right) \\
B_{67} &= \frac{\partial f}{\partial(M / R)} + \xi_a \frac{\partial f}{\partial V} \left([H + \delta H] \frac{dC_4}{dz^p} + [M / R + \delta M / R] \frac{dC_3}{dz^p} \right) \\
B_{77} &= \xi_a \frac{\partial f}{\partial V} \left(\frac{\partial f}{\partial V_0} \cdot \frac{dV_0}{dz^p} + \frac{\partial f}{\partial H_0} \cdot \frac{dH_0}{dz^p} + \frac{\partial f}{\partial(M_0 / R)} \cdot \frac{d(M_0 / R)}{dz^p} \right)
\end{aligned}$$

In general, structural analysis is done with a load : displacement relationship. Equation (19) can be achieved from equation (18), where $[s]^{-1}$ are easily obtained by elimination the seventh row of matrix $[B]$

$$\begin{Bmatrix}
\delta z \\
\delta h \\
R \delta \theta
\end{Bmatrix}
=
\begin{bmatrix}
s_{11} & s_{12} & s_{13} \\
s_{21} & s_{22} & s_{23} \\
s_{31} & s_{32} & s_{33}
\end{bmatrix}^{-1}
\begin{Bmatrix}
\delta V \\
\delta H \\
\delta M / R
\end{Bmatrix} \quad (19)$$

$$[s]^{-1} = \begin{bmatrix} B_{41} - \frac{B_{71} \cdot B_{47}}{B_{77}} & B_{42} - \frac{B_{72} \cdot B_{47}}{B_{77}} & B_{43} - \frac{B_{73} \cdot B_{47}}{B_{77}} \\ B_{51} - \frac{B_{71} \cdot B_{57}}{B_{77}} & B_{52} - \frac{B_{72} \cdot B_{57}}{B_{77}} & B_{53} - \frac{B_{73} \cdot B_{57}}{B_{77}} \\ B_{61} - \frac{B_{71} \cdot B_{67}}{B_{77}} & B_{62} - \frac{B_{72} \cdot B_{67}}{B_{77}} & B_{63} - \frac{B_{73} \cdot B_{67}}{B_{77}} \end{bmatrix} \quad (20)$$

Finally, a spudcan stiffness matrix which is used in the structural analysis expressed as equation (21) is obtained by inversion of equation (20)

$$\begin{Bmatrix} \delta V \\ \delta H \\ \delta M \end{Bmatrix} = \begin{bmatrix} S_{11} & S_{12} & S_{13} \\ S_{21} & S_{22} & S_{23} \\ S_{31} & S_{32} & S_{33} \end{bmatrix} \begin{Bmatrix} \delta z \\ \delta h \\ \delta \theta \end{Bmatrix} \quad (21)$$

Above all, structural analysis considering soil–structure effect can be performed with Model B, which is known as tangent stiffness method with elastic and elasto–plastic stiffness as well as yield surface.

6. Structural Analysis Considering Soil-Structure Interaction

In this chapter, an example of jack-up structural analysis taking soil-structure interaction effect into account is to be introduced. Pin, fix and spring are given as boundary conditions. Structural analysis results are compared to those done by (Martin, C.M., 1999).

Besides, WTIV structural analysis is also involved and the results are shown. Discussions about the results will also be followed.

6.1. An Example of Jack-Up Structural Analysis

6.1.1. Jack-up Model

Fig. 25 depicts a plane frame jack-up model with springs which consists of 6 nodes and 5 beam elements. There are two legs in the windward direction, so both beam properties and loads of the windward leg are the double of those of the leeward leg. It is assumed that self-weight are evenly distributed to each leg. The plane frame jack-up is modeled using Patran.

Fig. 25 Plane frame jack-up model with springs

Some main data for the example jack-up model and clay properties are listed in Table 5 and Table 6. Each leg is preloaded to 100 MN and after unloading its self-weight will be 50 MN. The diameter of the spudcan used here is 20 m. It should be noted that rigidity index, G/c_u , in Table 6 is used to calculate shear modulus of the clay which is a necessary coefficient in equations (8), (9), (10) and (14).

The jack-up model and properties are the same as those in

(Martin, C.M., 1994). Boundary conditions are set as pinned footings, fixed footings, includes SNAME footings and Model B footings.

Table 5 Data for the example jack-up model

Spudcan diameter B (m)	Total preload weight 3W (MN)	Total operation weight 3W (MN)
20	300	150

Table 6 Clay properties

Unit weight γ (kN/m ³)	Mudline strength s_{um} (kPa)	Increase with depth ρ (kPa/m)	Rigidity index G/s_u
19	10	1.4	100

Elastic stiffnesses of SNAME and Model B are listed in Table 7 and Table 8. These values take elastic soil stiffness factor into account. It should be noted again that since there are two legs in the windward direction, elastic stiffnesses of the windward spudcan are twice as much as those of the leeward spudcan.

Table 7 Elastic stiffnesses of SNAME

	K_1K_v (N/m)	K_2K_h (N/m)	K_3K_r (Nm)
Windward spudcan	7.54E+08	5.66E+08	6.29E+10
Leeward spudcan	3.77E+08	2.83E+08	3.14E+10

Table 8 Elastic stiffnesses of Model B

	K_1GR (N/m)	K_2GR (N/m)	K_3GR^3 (Nm)	K_4GR^2 (Nm)
Windward spudcan	6.20E+08	5.30E+08	4.70E+10	-4.36E+08
Leeward spudcan	3.10E+08	2.65E+08	2.35E+10	-2.18E+08

With the jack-up model above, structural analyses were performed as H_{env} was given from 0 MN to 10 MN with an interval of 1.25 MN. Both elastic and elasto-plastic spudcan behavior are considered with SNAME footings, but only elastic spudcan behavior is considered with Model B in this paper.

6.1.2. Jack-Up Structural Analysis Results

Structural analysis results of the example in this paper and in existing studies are shown in Fig. 26 and Fig. 27. Results with

SNAME footings and Model B footings are between fixed footings and pinned footings.

In Fig. 26(a), it can be seen that elastic behaviors with SNAME footings and Model B footings are the same. The point at which yield first occurs at leeward spudcan is almost the same around $H_{env}=5.4$ MN. Comparing SNAME footings results in this paper with the existing Model B footings results (Martin, C.M., 1999) shown in Fig. 27, it can be found that the maximum moment is almost the same. Yield and failure occurs at the same value of H_{env} . Fig. 26(a) illustrates a highly nonlinear behavior in moment.

In Fig. 26(b), vertical loads contain self-weight, weight of back-flow and the vertical load change to endure additional moment due to the environment. The vertical load difference between leeward spudcan and windward spudcan becomes smaller with spudcan fixity increasing. In elastic region, vertical load results of SNAME footings and Model B footings increase linearly, and their results are the same. However, after yielding, vertical load difference between leeward spudcan and windward spudcan increases nonlinearly. This is the reason why moment in leeward spudcan decreases immediately after yielding. Vertical load results

are almost the same as those in the existing studies.

Thus, it can be concluded that SNAME footings and Model B footings take the real soil behavior into account in the structural analysis and results show that moment decrease after yield when soil–structure interaction is considered, which cannot be found in conventional simplified pinned footings and fixed footings.

(a) Moment

(b) Vertical load

(c) Horizontal load

Fig. 26 Spudcan load results of this paper

(a) Moment

(b) Vertical load

(c) Horizontal load

Fig. 27 The existing spudcan load results

Combined stress results are listed in Fig. 28. It can be found that results with SNAME footings and Model B footings are almost the same.

From Fig. 26(b), we know that the vertical load difference between windward and leeward footings become larger with less spudcan fixity. With a similar horizontal load difference, a larger vertical load difference means a larger combined stress difference which is illustrated in Fig. 28.

(a) Fixed footings

(b) SNAME footings

(c) Model B footings

(d) Pinned footings

Fig. 28 Combined stress results

Fig. 29 depicts that hull sway is larger with less rotational stiffness at spudcan. Also, hull sway increases nonlinearly after yield occurs in leeward spudcan with environment load increasing.

Fig. 29 Hull sway

Fig. 30 depicts hull deformation results when environment load is 5 MN. From the results, hull deformations of SNAME footings and Model B footings are similar, and there is a large hull sway with pinned footings because of its lack of fixity. Thus, the structure should sustain more moments caused by environment load and this is the reason for large hull deformation.

(a) Fixed footings

(b) SNAME footings

Fig. 30 Hull deformation ($H_{env}=5$ MN)

6.2. WTIV structural analysis

6.2.1. WTIV Model

Fig. 31 shows the WTIV structural analysis model in this paper. It consists of four legs. WTIV hull structure is modeled as beam elements and a hypothetical spudcan is modeled under each leg. Dimensions of the WTIV are shown in Fig. 32. Boundary conditions are given at joint 2338, joint 2705, joint 3439 and joint 3702.

Structural analysis is performed using SACS program with a quasi-static environment load along the negative direction of y-axis given at the center of the hull from 0 MN to 12 MN with an interval of 1 MN.

Fig. 31 WTIV structural analysis model

The initial vertical load mainly caused by self-weight of WTIV, spudcan weight as well as payload which stands for the weight wind turbines. The self-weight of WTIV and spudcan weight are 76.231 MN and 3.688 MN, respectively, which distributed evenly through the hull and four spudcans. However, wind turbines are mainly placed at the center and after part of the ship, so the latter two endure more vertical loads than the two spudcans ahead when there is no environment load. The payload is 30.656 MN in this model.

Based on the three kinds of load, vertical load at each joint is

listed in Table 9. Thus, yield may first occur at one of the two latter spudcans with environment load increasing.

In this paper, based on the WTIV structural analysis model, joint 2338 and joint 3439 will be the leeward spudcans, while joint 2705 and joint 3702 will be the windward spudcans.

Table 9 Vertical load without environment load

Joint	2338	2705	3702	3439
V (MN)	30.148	30.173	25.139	25.114

6.2.2. Boundary Condition

Pinned footings, SNAME footings and fixed footings are given as boundary conditions to perform WTIV structural analysis case studies.

For SNAME footings, soil conditions of OW-3 and OW-4 are selected to calculate soil stiffnesses. In the previous Chapter 4, spudcan penetration under a preload of 50 MN was introduced (see Fig. 15). With the penetration depth factor, 2.42 in OW-3 and 0.73 in OW-4, elastic stiffness factor K_1, K_2, K_3 can be achieved with Fig. 35. Also, K_v, K_h, K_r can be obtained by equations (8), (9) and

(10). Thus, structural analysis can be performed with equation (11).

The elastic soil stiffness factor of SNAME curves shown in Fig. 32 are according to the effect of embedment of the spudcan on the elastic spring stiffness (Bell R.W., 1991; SNAME, 2002).

Fig. 32 Elastic soil stiffness factors of SNAME

Initial elastic stiffnesses of SNAME used in structural analysis are listed in Table 10.

Table 10 Initial elastic stiffnesses of SNAME

	K_1K_v (N/m)	K_2K_h (N/m)	K_3K_r (Nm)
OW-3	3.63E+08	2.80E+08	1.00E+10
OW-4	3.08E+08	2.74E+08	1.04E+10

6.2.3. WTIV Structural Analysis Results

Fig. 33 to Fig. 36 show the spudcan load results of each joint in both OW-3 and OW-4. From the moment results, it can be found that moment decreases immediately after yield occurs. Joint 2338 reaches yield and failure first, because it supports larger vertical load when environment load is not given and it is the leeward footing when the environment load is given. Thus, joint 2338 is the critical point.

Also, yield and failure occur at a lower H_{env} in OW-3 than in OW-4. This is mainly owing to that vertical load at the same H_{env} is larger in OW-3 than in OW-4. Moment results with SNAME footings lie between the pinned and fixed footings because there is some level of spudcan fixity.

From the moment and horizontal load results, before yield occurs (in elastic region), moment and horizontal load results of the leeward footings and windward footings are the same with the same kind of boundary conditions. However, difference between the results of the leeward and windward footings occurs after yield. This is due to that spudcan load will be redistributed due to the

soil–structure interaction effect.

(a) Moment

(b) Vertical load

(c) Horizontal load

Fig. 33 Spudcan loads in OW-3 (joint 2338 & joint 2705)

(a) Moment

(b) Vertical load

(c) Horizontal load

Fig. 34 Spudcan loads in OW-3 (joint 3439 & joint 3702)

(a) Moment

(b) Vertical load

(c) Horizontal load

Fig. 35 Spudcan loads in OW-4 (joint 2338 & joint 2705)

(a) Moment

(b) Vertical load

(c) Horizontal load

Fig. 36 Spudcan loads in OW-4 (joint 3439 & joint 3702)

Fig. 37 depicts the spudcan load path of H-M for joint 2338 in both OW-3 and OW-4. This figure explains the reason why yield and failure happen at a lower H_{env} in OW-3 is due to a higher value of V/V_{L0} and a lower value of c_u which leads to a lower value of H_{L0} . From the yield surface, after unloading, H-M envelope is smaller with a higher value of V/V_{L0} . What s more, due to the lower value of H_{L0} , elastic region becomes smaller, so yield and failure first occur in OW-3. Some useful data for yield surface of joint 2338 are shown in Table 11.

Fig. 37 Spudcan load path of H-M for joint 2338

Table 11 Data for yield surface of joint 2338

	D (m)	V_{L0} (MN)	V (MN)	V/V_{L0}	c_u (kPa)	H_{L0} (MN)
OW-3	29.04	71.59	51.738	0.72	22	4.10
OW-4	8.72	54.76	34.908	0.63	25	4.67

Fig. 38 illustrates spudcan load paths of V-M for OW-4. After preloading and unloading, spudcan vertical loads of joint 2338 and joint 2705 are 34.908 MN and 34.933 MN, respectively. With environment load increasing, vertical load in the windward spudcan

decreases while vertical in the leeward spudcan increases. In the elastic region, both moment and vertical load increase linearly. Yield first occurs in the leeward spudcan and moment decreases immediately after yield occurs. When the leeward spudcan reaches failure, the windward spudcan can still endure some level of moment.

Fig. 38 Spudcan load paths of V-M for OW-4

Fig. 39 depicts spudcan load paths of H-M for OW-4. The leeward spudcan first reaches its yield and moment decreases. After yielding in the leeward spudcan, its load combination remains

on the surface, and the H-M envelope contracts due to the increasing of vertical load in the leeward spudcan. However, in the case of the windward spudcan, the H-M envelope remains constant. It can be found from Fig. 39 that moment decreases after yielding, but horizontal load still increases.

Fig. 39 Spudcan load paths of H-M for OW-4

Fig. 40 shows Unity Check (UC) ratio results with pinned footings, SNAME footings and fixed footings. In general, structure members usually are subjected to including axial tension, axial

compression, shear force and bending moment at the same time. There is a load capacity for each force, and a combined load capacity for combined load condition. UC ratio is defined as the ratio of actual demand over the allowable capacity of the member. Combined UC results are calculated following AISC 9th/API 21st.

Maximum UC ratios are listed in Table 12 for upper and lower chord. From the results, in the case of upper chord, which is the member around leg-hull connection, maximum UC ratio is the largest when the boundary condition is given as pinned footings. It decreases with more spudcan fixity due to that spudcans endure more moments.

In the case of lower chord, however, UC ratio is the smallest when the boundary condition is given as pinned footings. It increases with more spudcan fixity because members at the lower chord sustain more moments.

Also, it should be noted that maximum UC ratios pinned footings and SNAME footings are similar mainly because when environment load H_{env} is 12 MN, the footings have already reached yield and lost some level of fixity. Thus, the SNAME footings under this condition are more like pinned footings.

(a) UC ratio results with pinned footings

(b) UC ratio results with SNAME footings

(c) UC ratio results with fixed footings

Fig. 40 WTIV UC ratio results

UC ratios of the members around the spudcan are smaller with less spudcan fixity. It can be seen that when the boundary conditions are set as fixed

Table 12 Maximum unity check ratio ($H_{env} = 12$ MN in OW-4)

	Pinned footings	SNAME footings	Fixed footings
Upper chord	0.422	0.41	0.213
Lower chord	0.131	0.141	0.27

7. Conclusion

There are mainly two issues considered in this paper. Spudcan penetration estimation was performed using conventional analysis recommended in SNAME guideline based on soil properties of OW-3 and OW-4. Based on spudcan penetration results, elastic stiffness factors were achieved which were used in structural analysis considering soil-structure interaction effect. An example jack-up and WTIV structural analysis were performed with pinned footings, spring footings and fixed footings.

From the spudcan penetration results, two distinctly different penetration depth were acquired. Punch-through possibility was assessed in OW-4 due to there is strong soil layer overlying soft soil layer. With spudcan penetration depth and effective spudcan diameter, elastic stiffness factors were acquired which were necessary for WTIV structural analysis.

Soil-structure interaction was introduced with SNAME footings and Model B footings. It can be considered by using soil stiffness and yield surface.

An example jack-up structural analysis was performed to study

the spudcan load distribution under different boundary conditions, pinned footings, SNAME footings, Model B footings and fixed footings. The results in this paper were compared and verified to those in existing studies, and the results with SNAME footings were highly consistent with those with Model B footings.

An in-place WTIV structural analysis was also performed with pinned footings, SNAME footings and fixed footings. A quasi-static environment load was given and boundary conditions were given at the hypothetical spudcans with soil stiffnesses. Case studies on spudcan load redistribution and yield surface were performed using soil conditions of OW-3 and OW-4. The structural analysis results show that with environment load increasing, leeward spudcans reaches yield and failure first, and moment decreases after yield occurs. Spudcan load curves become highly nonlinear after the leeward spudcan yielding. Also, due to a low value of undrained shear strength c_u and a high value of V/V_{L0} , yield occurs first in OW-3, which means that c_u and V/V_{L0} have a significant impact on yield surface and spudcan behavior. Lastly, spudcan fixity has the benefit of reducing the stresses of the members near leg-hull connection.

For further study, elasto-plastic spudcan behavior with Model B footings is intended. Dynamic structural analysis with different kinds of boundary conditions is also an important issue. Comparisons between the results with pinned footings and the results considering soil-structure interaction will be preferred.

Reference

- [1] Bell R.W. (1991). The Analysis of Offshore Foundations Subjected to Combined Loading, MSc Thesis, University of Oxford, UK.

- [2] Cassidy, M.J., Houlsby, G.T., Hoyle, M., Marcom, M.R. (2002). Determine appropriate stiffness levels for spudcan foundations using jack-up case records, 21st International Conference on Offshore Mechanics and Arctic Engineering, Olso, Norway, OMAE2002-28085.

- [3] Das, B.M. (2009). Principles of Geotechnical Engineering, 7th Edition, PWS Publishing Co., Boston.

- [4] Hansen J.B. (1970). A Revised and Extended Formula for Bearing Capacity, Bulletin No. 28, The Danish Geotechnical Institute.

- [5] Jun Zhao, Menglan Duan, Shijing Cao, Zhihui Hu, Linsong Song (2011). Prediction of spudcan penetration depth in multiple layers with sand overlying clay, Applied Mechanics and Materials Vols. 52-54, 995-1002.

- [6] Keith Nelson, Pharr Smith, Mike Hoyle, Richard Stonor, Thomas Versavel (2000). Jackup Response Measurements and the

Underprediction of Spud-Can Fixity By SNAME 5-5A, Offshore Technology Conference, Houston, USA, OTC 12074.

[7] Lindita Kellezi, Henrik Stadsgaard (2012). Design of Gravel Banks – A way to Avoid Jack-Up Spudcan Punch-Through Type of Failure, Offshore Technology Conference, Houston, USA, OTC 23184.

[8] Martin, C.M. (1994). Physical and Numerical Modelling of Offshore Foundations Under Combined Loads, D.Phil. Thesis, University of Oxford, UK.

[9] Martin, C.M., Houlsby, G.T. (1999). Jackup Unit on Clay: Structural Analysis With Realistic Modelling of Spudcan Behaviour, Offshore Technology Conference, Houston, USA, OTC 10996

[10] Martin, C.M., Houlsby, G.T. (2000). Combined loading of spudcan foundations on clay: laboratory tests, *Géotechnique* 50, No. 4, 325–338.

[11] Martin, C.M., Houlsby, G.T. (2001). Combined loading of spudcan foundations on clay: numerical modelling, *Géotechnique* 51, No. 8, 687–699.

[12] Ngo-Tran, C.L. (1996). The Analysis of Offshore Foundations Subjected to Combined Loading, D.Phil. Thesis, University of Oxford, UK.

- [13] SNAME (2002). Recommended Practice for Site Specific Assessment of Mobile Jack-Up Units, T&R Bulletin 5-5A, Society of Naval Architects and Marine Engineers, New Jersey, USA.
- [14] Youhu Zhang, Britta Bienen, Mark J. Cassidy (2014). Jack-up push-over analyses featuring a new force resultant model for spudcans in soft clay, Ocean Engineering 81, 139-149.
- [15] ZHANG Jian, TANG Wenxian, SU Shijie, GAO Chao (2012). Effects of Foundation Models on Jack-up Site Assessment, Advances in Natural Science, Vol. 5, No. 4, 12-18.

초록

해상풍력발전기 전문설치선 스퍼드캔의 토질-구조 연성에 관한 연구

해상풍력발전기를 효율적이게 설치하기 위하여 작업 타입 해상풍력발전기 전문설치선이 필요하다. 설치작업을 진행할 때 파랑의 작용을 없애기 위하여 선체를 해수면위로 들어올린다. 해상풍력발전기 전문설치선은 보통 여러개의 트러스 구조인 레그(leg)가 있다. 이러한 레그 아래 수직력과 수평력을 견딜 수 있는 뒤집힌 원뿔모양인 강구조물인 스퍼드캔(spudcan)이 있다.

해상풍력발전기 전문설치선이 안정적이게 설치 및 작업하기 위하여 작업 위치에서의 해저 토질 지지력에 대한 평가가 필요하다. 설치 위치에서 단단한 토질층아래 연약한 토질층이 있는 경우, 스퍼드캔이 예상치 못한 급격한 거동을 발생하는 가능성이 있는데 이러한 현상을 punch-through라고 한다. Punch-through가 발생하게 되면 한 쪽 레그에 과도한 힘이 걸리면서 선체구조가 파괴된다. 이러한 파괴를 방지하기 위하여 해저 토질의 지지력과 스퍼드캔의 관입 깊이에 대한 평가가 중요하다. 본 논문에서는 서남해안 해상풍력단지에서 실제 계측된

토질데이터를 바탕으로 미국조선학회에서 제시한 해석적 방법으로 평가를 진행하였다.

폭풍 상태에서의 해상풍력발전기 전문설치선의 구조평가가 또 하나의 중요한 문제다. 구조해석을 진행하기 위하여 보통 스퍼드캔 아래 토질의 복잡한 거동을 토질 강성도로 간략화한다. 이러한 토질 강성도를 구조해석시 선박의 경계조건으로 된다. 흔히 경계조건에서 핀(pin), 고정 및 스프링(spring)이 포함된다. 경계조건이 스프링인 경우, 미국조선학회에서 제시하는 방법과 Model B를 바탕으로 항복곡면을 이용하여 스퍼드캔의 토질-구조 연성 효과를 고려한다.

본 논문에서는 작업 2차원 모델을 이용하여 스퍼드캔 위치에서 각각 핀, 고정 및 스프링인 경계조건을 주어 구조해석을 진행하였다. 그 결과 미국조선학회에서 제시한 방법을 이용한 구조해석 결과와 기존 연구에서의 Model B를 이용한 구조해석 결과에 대하여 비교와 검증을 진행하였다. 두 가지 방법을 이용한 구조해석 결과가 비슷하다.

또한 본 논문에서는 해상풍력발전기 전문설치선 3차원 모델에 대하여 핀, 고정 및 스프링을 서남해안 두 가지 토질 조건에서의 케이스 스터디(case study)를 진행하였다. 결국 토질-구조 연성을 고려하는 경우 선체와 레그의 연결부에서 스트레스의 감소를 확인하였다. 또한 순풍 쪽의 스퍼드캔에서 항복이 먼저 발생하고 모든 스퍼드캔에 대하여 항복이 발생하게 되면 모멘트가 작아지며 토질강도와 예비하중이 구조해석 결과에 큰 영향을 준다.

주요어: 스퍼드캔(spudcan), 지지력, 토질-구조 연성, 토질 강성도,
향복곡면

학 번: 2012-23988